

STANDARD TFT LIST										
Part Number	Size (inch)	Resolution	Brightness (cd/m2)	Interface	Outline Dimensions (mm)	Active Area (mm)	Viewing Angle (U/D/L/R)	Operating Temperature	Min. LED Lifetime(Hours)	Special Feature
FUT0960Q07H	0.96	80 x 160	580	4-SPI	14.04*27.95*1.38	10.8 x 21.7	85/85/85/85	-20 to 70 °C	30k	IPS
FUT0110Q02H	1.09	240*240	300	4-SPI	30.59*32.98*1.56	27.79*27.79	85/85/85/85	-20 to 70 °C	30k	Round IPS
FUT0114Q020H	1.14	135*240	350	4-SPI	17.60*31.00*1.60	14.86*24.91	80/80/80/80	-20 to 70 °C	30k	Bar-type, IPS
FUT0128QV05B	1.28	240*240	350	MCU8	35.6*37.74*1.56	32.4*32.4	85/85/85/85	-20 to 70 °C	30k	Round IPS
FUT0130Q09B	1.30	240*240	300	MCU8	25.8*29.55*1.4	23.4*23.4	80/80/80/80	-20 to 70 °C	30k	Square, IPS
FUT0144Q013H	1.44	128*128	350	4-SPI	31.00*36.00*2.75	25.5*26.5	70/70/70/60	-20 to 70 °C	30k	TN
FUT0144Q017H	1.44	128*128	300	4-SPI	28.10*32.64*1.86	25.5*26.5	85/85/85/85	-20 to 70 °C	30k	IPS
FUT0154Q12H	1.54	240*240	380	MCU8/4-SPI	31.52*33.72*1.98	27.72*27.72	80/80/80/80	-20 to 70 °C	30k	Square, IPS
FUT0177QQ08S	1.77	128*160	260	4-SPI	34.7*46.7*3.45	28.03*35.04	45/45/45/20	-20 to 70 °C	30k	TV,For POS, TN+RTP
FUT0185QV02B	1.85	240*284	380	4-SPI	31.4*39.23*1.85	29.52*34.93	85/85/85/85	-20 to 70 °C	30k	Four sides of the arc chamfer, IPS
FUT0190QG04B	1.90	170*320	430	4-SPI	25.8*49.72*1.43	22.7*42.72*1.43	80/80/80/80	-20 to 70 °C	30k	Bar-type,IPS
FUT0200QV28H	2.00	240*320	250	MCU16	34.6*47.8*2.05	30.6*40.8	85/85/85/85	-20 to 70 °C	30k	IPS
FUT0200QV35B	2.00	320*240	260	4-SPI	46.10*40.96*2.53	40.80*30.60	80/80/80/80	-20 to 70 °C	30k	landscape, IPS
FUT0200VG38B	2.00	480*360	280	MIPI-2L	46.10*40.96*2.53	40.82*30.62	80/80/80/80	-20 to 70 °C	30k	landscape, HD IPS
FUT0210VWV04B	2.10	480*480	300	RGB+3-SPI	56.18*59.71*2.30	53.28*53.28	85/85/85/85	-20 to 70 °C	30k	Round IPS
FUT0230QV18H	2.31	320*240	200	4-SPI	55.20*47.55*2.8	46.75*35.06	70/70/70/60	-20 to 70 °C	30k	landscape, TN
FUT0240QV32S	2.40	240*320	350	MCU/SPI/RGB	42.72*60.26*2.35	36.72*48.96	65/65/65/45	-20 to 70 °C	30k	All interface compatible, TN
FUT0240Q094B	2.40	128*160	320	4-SPI	42.72*60.26*2.35	36.71*48.96	85/85/85/85	-20 to 70 °C	30k	IPS
FUT0240QV103B	2.40	240*320	320	MCU8/16	42.32*59.91*2.4	36.72*48.96	80/80/80/80	-20 to 70 °C	30k	IPS
FUT0280QV67S	2.80	240*320	300	4-SPI	50.00*69.20*2.3	43.20*57.60	65/65/65/45	-20 to 70 °C	30k	EWV TN
FUT0280QV156B	2.80	240*320	330	4-SPI	50.00*69.20*2.35	43.20*57.60	80/80/80/80	-20 to 70 °C	30k	IPS
FUT0286QH07B	2.86	376*960	230	RGB+3-SPI	43.04*74.91*2.2	36.72*65.28	80/80/80/80	-20 to 70 °C	30k	Bar-type, IPS, CTP available
FUT0300VWV06H	3.00	360*640	350	MIPI-2L	56.54 x 84.96 x 2.2	48.96 x 73.44	80/80/80/80	-20 to 70 °C	30k	IPS
FUT0320QV04H	3.20	240*320	230	MCU16	55.04*77.7*2.5	48.60*64.80	65/65/65/45	-20 to 70 °C	30k	EWV TN
TFT3.5-118	3.50	320*480	450	MCU16	55.50*84.95*3.65	48.96*73.44	70/60/70/60	-20 to 70 °C	30k	EWV TN +RTP
FUT0350HV67B	3.50	320*480	300	RGB+3-SPI	54.38*84.61*2.00	48.96*73.44	85/85/85/85	-20 to 70 °C	30k	IPS
FUT0350WV52B	3.50	480*800	300	RGB+3-SPI	51.32*86.61*2.15	45.36*75.60	85/85/85/85	-20 to 70 °C	30k	HD IPS, CTP available
FUT0350QV95Q	3.50	320*240	380	RGB+3-SPI	76.9*63.9*3.1	70.08x 52.56	45/45//15/35	-20 to 70 °C	30k	landscape, TN
FUT0350VG41S	3.50	480*480	350	MIPI-4L	76.84*63.75*3.07	70.08*52.56	85/85/85/85	-20		